

STURGO®

High Lift Pallet Jack



Usage

Ideal for situations where pallets need to be transferred to low-raised shelving or storage; or to lift pallets to a safe working height for production, assembly, packing and distribution, reducing injuries caused by bending and reaching.

Features & Benefits

- Reduce injuries caused by bending, reaching and lifting - lifts up to 800mm high
- Easy to operate and ideal for shorter distance travel
- Manual lever pump action lift, gentle lowering action
- Scissor support legs for stability with unevenly loaded pallets
- Economical and efficient
- Durable, powder-coated finish
- Available in 520mmW or 685mmW fork widths

Specifications

Model 16810010

Max. Lift Height: 800mm
 Min. Lift Height: 85mm +/- 2mm
 Max. Load Capacity: 1000kg
 External Fork Width: 520mm
 Internal Fork Width: 196mm
 Fork Length: 1140mm
 Unit Weight: 105kg
 Lifting Speed: 9mm per stroke (0.1mm/second)

Model 16810011

Max. Lift Height: 800mm
 Min. Lift Height: 85mm +/- 2mm
 Max. Load Capacity: 1000kg
 External Fork Width: 680mm
 Internal Fork Width: 356mm
 Fork Length: 1140mm
 Unit Weight: 112kg
 Lifting Speed: 9mm per stroke (0.1mm/second)

